




CSN® HEATING CORD

CSN®-heating cords are used as heat carrier in electric head pads, electric blankets, heat mats and electric appliances.

Owing to its high flexibility, this heating cord is especially suited for very narrow installation radius.

The insulation material of this heating conductor consists of braided glass silk threads or plastic injection sheathing.

TYPE HKGK, WITH GLASS SILK INSULATION, CONFECTIONED



Standard version:

Constantan wire

with 4 glass silk wrappings

with 1 glass silk braiding


Cable ends closed with cable shoes

Colour marking: white

Temperature resistance 250 °C

Nominal voltage 230 V~

Installation: Don't wind heating cord one on top of the other.



Type	Width mm	Length mm	Capacity Watt	Voltage Volt
HKGk 005	0,5	3,5	17,5	230
HKGk 010	1,0	3,5	35,0	230
HKGk 020	2,0	3,5	70,0	230
HKGk 030	3,0	3,5	105,0	230
HKGk 050	5,0	3,5	175,0	230
HKGk 100	10,0	3,5	350,0	230

Specialist contact person:

Andreas Nottelmann

Phone: +49 2392 - 692 - 35

Fax: +49 2392 - 692 - 8935

eMail: andreas.nottelmann@schniewindt.de

Dominik Naumann

Phone: +49 2392 - 692 - 61

Fax: +49 2392 - 692 - 8961

eMail: dominik.naumann@schniewindt.de